



Power generator

F 6001

Nr art. 33833

Characteristic

- Voltage stabilization +5 -10 %
- Low level of THD ≤ 6 %
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP IP 23
- Full single phase power output socket 32 Amps

Technical parameters

Frequency	50 Hz
Voltage	230 V
Maximum power	6,6 kW
Nominal power	6,0 kW
Prime current	26,1 A
Engine	Rato
Model	R 420
Capacity	420 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,1 L
Starting system	Manual
Fuel	Petrol
Fuel tank	6,5 L
Consumption (load 75%)	2,9 L / h
Noise level Lwa	99 dB(A)
Weight	69 kg
Length	790 mm
Width	580 mm
Height	505 mm

Standard equipment

- Socket 230 V 16 A
- Socket 230 V 32 A
- Overload protection
- Oil level sensor

Optional and service equipment

- Exhaust hose Nr art. 15876
- Exhaust adapter Nr art. 10118
- Hourmeter Nr art. 23300
- Transportation set Nr art. 28807
- Service kit Nr art. 35111
(air filter, spark plug, engine oil)

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EC Directive